



*...competitive technologies
with compelling value*

CT-HDVRD-HDWR-KIT

HD Wireless Transmitter & Receiver Kit

Up to 400' Line of Sight Transmission

Features:

- Transmits an HDMI signal from source device to a display device up to 400' with line of sight or 150' through normal buildings
- Full HD 1080p transmission
- Compliant with HDMI and HDCP
- Supports IR remote control function to source device
- No cabling is required between transmitter and receiver
- Low profile design with an simple and clean installation



Description:

The CT-HDVRD-HDWR-KIT is a long range wireless HDbitT HDMI AV transmitter that can extend high definition audio and video to any HDTV display up to 400' away with line of sight or 150' through normal buildings. It supports HD resolutions up to 1080p and provides remote transmission of infrared control from the monitoring device to the source device. The CT-HDVRD-HDWR-KIT is the perfect solution for distributing high definition video and audio in locations where wires can not be run. Up to two total receive units can be used with a single transmission unit.

Specifications:

HDMI signal	HDCP compatible
Transport protocol	HDbitT
Supported resolutions	480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz
IR remote control	Supports 20 - 60kHz IR remote device
Transmission frequency	5.8 GHz
Transmission distance	400' at 1080p 60Hz with line of sight 150' at 1080p 60Hz through a normal building
Working temperature	0°C - 60°C
Power supply	DC5V/2A
Transmitter power consumption	<8.5W
Receiver power consumption	<5.5 W
Housing material	Metal
Transmitter dimensions	7.70"W x 5.42"D x 1.22"H
Receiver dimensions	7.70"W x 5.42"D x 1.22"H
Transmitter weight	1.17 lbs.
Receiver weight	1.16 lbs.
Color	Black

Ordering Information:

CT-HDVRD-HDWR-KIT	Wireless HDMI Transmitter & Receiver Kit
CT-HDVRD-HDWR-RX	Additional HDMI Wireless Receiver

CT-HDVRD-HDWR-KIT Package Contents:

1	HDMI Transmitter
1	HDMI Receiver

Email: sales@cabletronix.com

Web: www.cabletronix.com