

HAC-HFW2220S

2.4Megapixel 1080P Water-proof HDCVI IR-Bullet Camera



Features:

- 1/2.8" 2.4Megapixel CMOS
- 25/30fps@1080P, 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- DWDR, Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens
- Max. IR LEDs length 30m, Smart IR
- IP67, DC12V



Specifications:

Camera

Image Sensor	1/2.8" 2.4Megapixel CMOS
Effective Pixels	1984(H) × 1225(V)
Electronic Shutter	1/3s~1/100,000s
Video Frame Rate	25/30/50/60fps@720P; 25/30fps@1080P
Synchronization	Internal
Min. Illumination	0.05Lux@F1.2(AGC ON), 0Lux IR on
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)

Camera Features

Max. IR LEDs Length	100', Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Supported

Lens

Focal length	3.6mm
Angle of View	H: 53.4°(88°/39°)
Mount Type	M12

General

Power Supply	DC12V±10%
Power Consumption	Max 4.8W
Working Environment	-22°F~+140°F / Less than 95%RH (no condensation)
Transmission Distance	Over 1,600' via coaxial cable
Ingress Protection	IP67
Dimensions(W×D×H)	2.56" x 6.1"
Weight	0.85lbs.
Housing Material	Metal

Ordering Information:

HAC-HFW2220S 2.4Megapixel 1080P Water-proof HDCVI IR-Bullet Camera

North American Cable Equipment Inc.

(800) 688-9282 email: sales@northamericancable.com www.northamericancable.com