

Features:

- RS485 Bus Line and keyboard can connect to up to 31 dome cameras.
- Compatible with most control protocols.
- Controls Iris, Focus and Zoom.
- Set and call presets, run scanning patterns and tours.
- Matrix control enables controlling domes indirectly.
- Equipped with 3D Joystick and LCD screen.
- LCD can display current operation orders, protocol name, current dome ID, current monitor ID and the state of the joystick.

Specifications:

Communication:	RS485, IR remote
Communication Distance:	RS485, 4,000 Feet
Baud Rate:	2400,4800,9600,19200 bps optional
Protocol:	Pelco-P/Pelco-D
Power Supply:	DC12V, 250MA
Operating Temperature:	14°F to 131°F
Dimensions:	6.6"L x 5.35"W x 4.1"H

ST-PTZMINI-KB Miniature Keyboard Controller



Ordering Information:

ST-PTZMINI-KB Miniature Keyboard Controller

Specifications:

Communication Protocol:	RS-485 Half-Duplex
Communication Distance:	Up to 3,900 Feet
Baud Rate:	1200, 2400, 4800, 900 and 19200 Bits/S
Interface:	5 Pin pressure line terminal
Operating Temperature:	14°F - 131°F
Relative Humidity:	<90%
Power Supply:	12VDC, 2A
Dimensions:	12" x 5.8" x 3.2"
Weight:	1.5 lbs.

ST-PTZ-KB PTZ Keyboard Controller



The ST-PTZ-KB is a professional grade pan, tilt, zoom (PTZ) controller for up to 255 PTZ-enabled CCTV cameras and other devices. The unit uses RS-485 communications, includes an LCD display and a 3-axis joystick. Single key protocol and baud rate retrieval of a current control address is an innovative feature. Password protected to lock out unauthorized users.

Ordering Information:

ST-PTZ-KB Keyboard Controller

Features:

- LCD Screen
- Baud rate option
- Backlit keys
- Three axis optical joystick
- Two RS485 ports and DVR port
- Capable of controlling up to 32 high speed domes and 16 DVRs
- DVR control: image shift, record, stop, play, image zoom, catch screen, speed up, back, menu, alarm, etc.



Specifications:

Power Supply:	DC9V/5W
Communication:	RS485
Distance:	4,000'
Protocol:	PELCO-D, PELCO-P, MOLYNX
Baud Rate:	2,400, 4,800, 9,600, 19,200
Max Controllable Cameras:	32 pcs.
Display:	LCD
Direction Control:	Three Axis
Dimensions:	5.5"H x 14.6"W x 10.7"D
Weight:	5.75 lbs.

Ordering Information:

ST-PTZ33 Keyboard Controller

Features:

- Includes 1 handheld infrared remote control & 1 PT dome controller
- Power supply for PT dome controller and batteries for remote control not included
- Allows for PTZ control of up to 255 PTZ cameras
- Supports PELCO-D / P

Ordering Information:

ST-PTZ-RC Infrared Remote PTZ Controller

