



Features:

- 1/3" CMOS Sensor
- 3.6mm Fixed lens
- 600 TV Lines
- 0.1 Lux Color / 0.0 Lux B&W
- Three axis mount
- Cable hidden bracket design
- 66' Infrared range
- Super back light compensation
- IP66 Water Resistance

Ordering Information:

ST-BT6003.6-B2 Camera With 3.6mm Lens & Black Housing
ST-BT6003.6-W2 Camera With 3.6mm Lens & White Housing

Securitytronix Bullet Cameras

Color Infrared Weatherproof Bullet Camera With CMOS Sensor

Specifications:

Image Sensor	1/3" Digital Image Sensor
Effective Picture Elements	NTSC: 728(H)×488(V)
Horizontal Resolution	600TV Line
Minimum Illumination	0.1 Lux Color, 0.0 Lux B/W 0 Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning Type	Interlaced Scanning
Electronic Shutter Time	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
Number Of IR LEDs	24
IR Distance	66 Feet (with Infrared LED)
IR Cut	Auto
BLC	Super Back Light Compensation
White Balance	Auto
Video Output	1Vpp, 75Ω
Power/Current	DC12V/350mA
Lens	3.6mm Fixed Lens
Weather Rating	IP66
Dimensions	3.25"W x 2.4"H x 5.2"D
Weight	14.1 Ounces
Storage Temperature	-10°F to +140°F
Operating Temperature	+20°F to +110°F
Warranty	1 Year



Features:

- 1/3" CMOS Sensor
- 600 TV Lines
- 3.6mm or 6.0mm Fixed lens
- 0.1 Lux Color, 0.05 Lux B/W
- Two axis mount
- Super back light compensation
- Indoor Housing

Ordering Information:

ST-D6003.6-B Camera With 3.6mm Lens & Black Housing
ST-D6003.6-W Camera With 3.6mm Lens & White Housing
ST-D6006-B Camera With 6.0mm Lens & Black Housing
ST-D6006-W Camera With 6.0mm Lens & White Housing

Securitytronix Dome Cameras

Indoor Color Dome Camera With CMOS Sensor

Specifications:

Image Sensor	1/3" Digital Image Sensor
Effective Picture Elements	NTSC: 768(H)×494(V)
Horizontal Resolution	600TV Line
Minimum Illumination	0.1 Lux Color, 0.05 Lux B/W
S/N Ratio	>63.8dB (AGC Off)
Scanning Type	Interlaced Scanning
Electronic Shutter Time	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.15
BLC	Super Back Light Compensation
White Balance	Auto
Video Output	1Vpp, 75Ω
Power/Current	DC12V/750mA
Lens	3.6 or 6.0mm Fixed Lens
Storage Temperature	-4°F to +140°F
Operating Temperature	+14°F to +122°F
Warranty	1 Year