



### Features:

- 1/3" CMOS Sensor
- 3.6mm Fixed lens
- 700 TV Lines
- 0.1 Lux Color / 0.0 Lux B/W
- Three axis mount
- Cable hidden bracket design
- 66' Infrared range
- Super back light compensation
- IP66 Water Resistance

### Ordering Information:

ST-BT7003.6-B2 Camera With 3.6mm Lens & Black Housing  
ST-BT7003.6-W2 Camera With 3.6mm Lens & White Housing

## Securitytronix Bullet Cameras

### Color Infrared Weatherproof Bullet Camera With CMOS Sensor

#### Specifications:

|                            |                                                      |
|----------------------------|------------------------------------------------------|
| Image Sensor               | 1/3" Digital Image Sensor                            |
| Effective Picture Elements | NTSC: 728(H)×488(V)                                  |
| Horizontal Resolution      | 700TV Line                                           |
| Minimum Illumination       | 0.1 Lux Color, 0.0 Lux B/W<br>0 Lux (with IR LED ON) |
| S/N Ratio                  | >48dB                                                |
| Scanning Type              | Interlaced Scanning                                  |
| Electronic Shutter Time    | NTSC: 1/60s~1/100,000s                               |
| Gamma Characteristic       | 0.45                                                 |
| Number Of IR LEDs          | 24                                                   |
| IR Distance                | 66 Feet (with Infrared LED)                          |
| IR Cut                     | Auto                                                 |
| BLC                        | Super Back Light Compensation                        |
| White Balance              | Auto                                                 |
| Video Output               | 1Vpp, 75Ω                                            |
| Power/Current              | DC12V/350mA                                          |
| Lens                       | 3.6mm Fixed Lens                                     |
| Weather Rating             | IP66                                                 |
| Dimensions                 | 3.25"W x 2.4"H x 5.2"D                               |
| Weight                     | 14.1 Ounces                                          |
| Storage Temperature        | -10°F to +140°F                                      |
| Operating Temperature      | +20°F to +110°F                                      |
| Warranty                   | 1 Year                                               |



### Features:

- 1/3" CMOS Sensor
- 600 TV Lines
- 3.6mm or 6.0mm Fixed lens
- 0.1 Lux Color, 0.05 Lux B/W
- Two axis mount
- Super back light compensation
- Indoor Housing

### Ordering Information:

ST-D6003.6-B Camera With 3.6mm Lens & Black Housing  
ST-D6003.6-W Camera With 3.6mm Lens & White Housing  
ST-D6006-B Camera With 6.0mm Lens & Black Housing  
ST-D6006-W Camera With 6.0mm Lens & White Housing

## Securitytronix Dome Cameras

### Indoor Color Dome Camera With CMOS Sensor

#### Specifications:

|                            |                               |
|----------------------------|-------------------------------|
| Image Sensor               | 1/3" Digital Image Sensor     |
| Effective Picture Elements | NTSC: 768(H)×494(V)           |
| Horizontal Resolution      | 600TV Line                    |
| Minimum Illumination       | 0.1 Lux Color, 0.05 Lux B/W   |
| S/N Ratio                  | >63.8dB (AGC Off)             |
| Scanning Type              | Interlaced Scanning           |
| Electronic Shutter Time    | NTSC: 1/60s~1/100,000s        |
| Gamma Characteristic       | 0.15                          |
| BLC                        | Super Back Light Compensation |
| White Balance              | Auto                          |
| Video Output               | 1Vpp, 75Ω                     |
| Power/Current              | DC12V/750mA                   |
| Lens                       | 3.6 or 6.0mm Fixed Lens       |
| Storage Temperature        | -4°F to +140°F                |
| Operating Temperature      | +14°F to +122°F               |
| Warranty                   | 1 Year                        |