

Securitytronix Bullet Cameras

Wide Dynamic Range Weatherproof Color Infrared Camera



Features:

- SONY 1/3" Super HAD CCD Sensor
- Digital Wide Dynamic Range (DWDR)
- 3.6mm Lens
- 600 TV Lines
- 0 Lux
- On screen display
- Three axis mount
- Cable hidden bracket design
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Gamma Characteristic 0.45
- IP66 Water Resistance

Specifications:

Pick up Element	1/3" SONY Super HAD CCD
Effective Picture Elements	NTSC: 811(H)×508(V)
Horizontal Resolution	600TV Line
Minimum Illumination	0.001 Lux; 0Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	130 Feet (with Infrared LED)
IR Status	Under 10Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/600mA
Lens	Board Lens 3.6mm/F2.0
Dimension	7.9"(W) x 3.0"(H) x 3.2"(D)
Weight	1.75 lbs
Storage Temperature	-22°F to +140°F
Operating Temperature	-14°F to +113°F
Warranty	1 Year

Ordering Information:

ST-BTWD600IR40-W	White Housing
ST-BTWD600IR40-B	Black Housing



Features:

- SONY 1/3" Super HAD CCD Sensor
- Digital Wide Dynamic Range (DWDR)
- Varifocal 2.8 - 12mm Lens
- 650 TV Lines
- 0 Lux
- Integrated tuning tools for focus & zoom
- On screen display
- Three axis mount
- Cable hidden bracket design
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Dual voltage: 12VDC / 24VAC
- IP66 Water Resistance
- Includes extension adapter

Wide Dynamic Range Weatherproof Color Infrared Camera

Specifications:

Pick up Element	1/3" SONY Super HAD CCD
Effective Picture Elements	NTSC: 811(H)×508(V)
Horizontal Resolution	650TV Line
Minimum Illumination	0.001 Lux; 0Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	160 Feet (with Infrared LED)
IR Status	Under 10Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current (IR Off)	DC12V-130mA / AC24V-70mA
Power/Current (IR On)	DC12V-600mA / AC24V-220mA
Lens	2.8 - 12mm Manual zoom lens
Dimension	10.2"(W) x 6.3"(H) x 4.1"(D)
Weight	3.3 lbs
Storage Temperature	-22°F to +140°F
Operating Temperature	-14°F to +113°F
Warranty	1 Year

Ordering Information:

ST-BTWD650IR2812-W	White Housing
ST-BTWD650IR2812-B	Black Housing

**New OSD
Controller**

