



Features:

- SONY 1/3" Super HAD CCD Sensor
- Digital Wide Dynamic Range (DWDR)
- 3.6mm Lens
- 650 TV Lines
- 0 Lux
- On screen display
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Gamma Characteristic 0.45
- Indoor plastic housing

Ordering Information:

ST-DWD650IR-B
ST-DWD650IR-W

Securitytronix Dome Cameras

Wide Dynamic Range Infrared Color Dome Camera

Specifications:

Pick up Element	1/3" SONY Super HAD CCD Sensor
Effective Picture Elements	NTSC: 811(H)×508(V)
Horizontal Resolution	650TV Line
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED On)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	65 Feet (with Infrared LED)
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/400mA
Lens	3.6mm Board Lens
Dimension	3.75"(W) x 2.75"(H)
Weight	1.0 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year

Black Housing
White Housing



Features:

- SONY 1/3" CCD Sensor
- 3.6mm Lens
- 650 TV Lines
- 0 Lux
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Built-In Auto Electronic Shutter (AES) up to 1/100,000s.
- Gamma Characteristic 0.45
- IP65 Water Resistance

Ordering Information:

ST-D650IRVP-B Black Housing
ST-D650IRVP-W White Housing

Securitytronix Dome Cameras

Vandalproof IR Color Dome Camera

Specifications:

Pick up Element	1/3"SONY
Effective Picture Elements	NTSC: 768(H)×494(V)
Horizontal Resolution	650TV Line
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED On)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	65 Feet (with Infrared LED)
IR Status	Under 10 Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/400mA
Lens	3.6mm Board Lens
Dimension	3.75"(W) x 2.75"(H)
Weight	1.0 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year

North American Cable Equipment Inc. (800) 688-9282 Fax: (800) 230-1793

email: sales@securitytronix.com web: www.securitytronix.com www.northamericacable.com