



Features:

- SONY 1/3" CCD Sensor
- 2.8-12.0mm Manual zoom lens
- 650 TV Lines
- 0 Lux
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Built-In Auto Electronic Shutter (AES) up to 1/100,000s.
- Gamma Characteristic 0.45
- IP65 Water Resistance

Ordering Information:

ST-DLI650IRVP2812-B	Black Housing
ST-DLI650IRVP2812-W	White Housing
ST-JBX-B	Junction box, black
ST-JBX-W	Junction box, white

Securitytronix Dome Cameras

Low Illumination Vandalproof IR Color Dome Camera

Specifications:

Pick up Element	1/3"SONY
Effective Picture Elements	NTSC: 768(H)×494(V)
Horizontal Resolution	650TV Lines
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	100 Feet (with Infrared LED)
IR Status	Under 10 Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/500mA
Lens	2.8-12mm Manual Zoom Lens
Dimension	5.16"(W) x 3.7"(H)
Weight	1.9 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year



**Optional
Junction
Boxes Also
Available**



Features:

- SONY 1/3" CCD Sensor
- 4.0-9.0mm Manual zoom lens
- 540 TV Lines
- 0 Lux
- 3 Axis mount
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Built-In Auto Electronic Shutter (AES) up to 1/100,000s.
- Gamma Characteristic 0.45
- IP65 Water Resistance

Ordering Information:

ST-DLI540IRVP49-S	Silver Housing
-------------------	----------------

Low Illumination Vandalproof IR Color Dome Camera

Specifications:

Pick up Element	1/3"SONY
Effective Picture Elements	NTSC: 768(H)×494(V)
Horizontal Resolution	540TV Line
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	65 Feet (with Infrared LED)
IR Status	Under 10 Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/400mA
Lens	4-9mm Manual Zoom Lens
Dimension	5.9"(W) x 3.9"(H)
Weight	2.9 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year