

Vandalproof Color Wide Dynamic Range Dome Camera

Features:

- SONY 1/3" Super HAD CCD Sensor
- 2.8mm - 12mm Manual Zoom lens
- 650 TV Lines
- 0.001 Lux
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Built-In Auto Electronic Shutter (AES) up to 1/100,000s.
- Gamma Characteristic 0.45
- Wide Dynamic Range (WDR)
- On Screen Display
- IP65 Weather Rating



The ST-DLI650VPDV2812 is a dual voltage vandalproof wide dynamic range color dome camera designed around a 1/3" SONY Color Super HAD CCD with 650TVL of resolution. The camera's 2.8mm – 12mm manual zoom lens provides an optimal field of view. The ST-DLI650VPDV2812's size and packaging allow it to be easily and discretely installed. Its rich color, high definition and stability make it attractive for CCTV security applications.

The ST-DLI650VPDV2812 requires a minimum 12VDC 300mA power supply such as the ST-PS12VDC1A or ST-PS12VDC2A. Since this is a dual voltage camera a 24V AC power supply such as the ST-PS24VAC can also be used.

Specifications:

Image Sensor	1/3" SONY Super HAD CCD
Pixels (HxV)	811 x 508
Scanning System	NTSC
Horizontal Resolution	650TV Lines
Synchronization	Internal, Negative Sync
Minimum Illumination	0.001Lux
Scanning System	2 :1 interlace
Auto Electronic Shutter	1/60s ~ 1/100,000s
Auto Gain Control	Automatic
Lens	2.8mm -12mm manual zoom lens
S/N Ratio	>48dB
Gamma Characteristic	0.45
Video Output	1.0Vp-p / 75Ω
Operation Temperature	14°F - 113°F
Relative Humidity	95% maximum
Weather Rating	IP65
Power Requirements	AC24V / DC12V 300mA
Dimensions	5.5" x 4.7"
Weight	1.95 lbs
Warranty	2 Years

Ordering Information:

ST-DLI650VPDV2812-B	Black Housing
ST-DLI650VPDV2812-W	White Housing

Package Contents:

1	ST-DLI650VPDV2812 Camera
1	Mounting hardware
1	Instruction manual