

Features:

- SONY 1/3" CCD Sensor
- 2.8-12.0mm Manual zoom lens
- 800 TV Lines
- 0 Lux
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Built-In Auto Electronic Shutter (AES) up to 1/100,000s.
- Gamma Characteristic 0.45
- IP65 Water Resistance

Specifications:

Pick up Element	Sony 1/3" CCD Sensor
Effective Picture Elements	NTSC: 768(H)×494(V)
Horizontal Resolution	800 TV Lines
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	100 Feet (with Infrared LED)
IR Status	Under 10 Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/500mA
Lens	2.8-12mm Manual Zoom Lens
Dimension	5.16"(W) x 3.7"(H)
Weight	1.9 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	2 Years

Ordering Information:

ST-DLI800IRVP2812-B	Black Housing
ST-DLI800IRVP2812-W	White Housing

