

Securitytronix Dome Cameras

**Wide Dynamic Range
Vandalproof IR Color Dome Camera**

Features:

- SONY 1/3" Sensor
- Digital Wide Dynamic Range (DWDR)
- 2.8-12.0mm Manual zoom lens
- 1,000 TV Lines, 720p
- 0.01 Lux, 0 Lux with IR LED on
- On screen display
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Gamma Characteristic 0.45
- IP65 Water Resistance



Specifications:

Pick up Element	1/3" SONY Sensor
Effective Picture Elements	NTSC: 1,280(H)×720(V)
Horizontal Resolution	1,000 TV Lines (720p)
Minimum Illumination	0.01 Lux; 0 Lux (with IR LED ON)
S/N Ratio	>52dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	100 Feet (with Infrared LED)
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/600mA
Lens	2.8-12mm Manual Zoom Lens
Dimension	5.16"(W) x 3.7"(H)
Weight	1.9 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year

Ordering Information:

ST-DWD1000IRVP2812-B
ST-DWD1000IRVP2812-W

Black Housing
White Housing