



Features:

- SONY 1/3" Super HAD CCD Sensor
- Digital Wide Dynamic Range (DWDR)
- 2.8-12.0mm Manual zoom lens
- 650 TV Lines
- 0 Lux
- On screen display
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Gamma Characteristic 0.45
- IP65 Water Resistance
- Includes junction box for hiding connections

Ordering Information:

ST-DWD6502812-JBX-B
ST-DWD6502812-JBX-W

Wide Dynamic Range Vandalproof IR Color Dome Camera

Specifications:

Pick up Element	1/3"SONY Super HAD CCD Sensor
Effective Picture Elements	NTSC: 811(H)×508(V)
Horizontal Resolution	650 TV Lines
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	100 Feet (with Infrared LED)
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/500mA
Lens	2.8-12mm Manual Zoom Lens
Dimension	5.16"(W) x 3.7"(H)
Weight	1.9 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year

Black Housing
White Housing



Features:

- SONY 1/3" CCD Sensor
- 2.8-12.0mm Manual zoom lens
- 650 TV Lines
- 0 Lux
- Built-in auto gain control (AGC) circuit allows this camera to produce a high definition picture in low light conditions
- Built-In Auto Electronic Shutter (AES) up to 1/100,000s.
- Gamma Characteristic 0.45
- IP65 Water Resistance
- Includes junction box for hiding connections

Ordering Information:

ST-DLI6502812-JBX-B Black Housing
ST-DLI6502812-JBX-W White Housing

Securitytronix Dome Cameras Low Illumination Vandalproof IR Color Dome Camera

Specifications:

Pick up Element	1/3"SONY
Effective Picture Elements	NTSC: 768(H)×494(V)
Horizontal Resolution	650TV Lines
Minimum Illumination	0.001 Lux; 0 Lux (with IR LED ON)
S/N Ratio	>48dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s
Gamma Characteristic	0.45
IR Distance	100 Feet (with Infrared LED)
IR Status	Under 10 Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vpp, 75Ω
Auto Gain Control	Auto
Power/Current	DC12V/500mA
Lens	2.8-12mm Manual Zoom Lens
Dimension	5.16"(W) x 3.7"(H)
Weight	1.9 lbs.
Storage Temperature	-22°F to +140°F
Operating Temperature	+14°F to +113°F
Warranty	1 Year

North American Cable Equipment Inc. (800) 688-9282 Fax: (800) 230-1793

email: sales@securitytronix.com web: www.securitytronix.com www.northamericacable.com