

ST-EVO-BT3.6 IP Indoor Bullet Camera, Fixed Lens

Features:

- 1/3" CMOS Sensor
- 300,000 Pixel
- MJPEG Compression
- WiFi Capable
- 3.6mm Lens
- 65 Foot IR capability
- IP66 Outdoor housing
- Power supply included



Specifications:

Features	System Security	Supports three-level account, password, user authority management
	Cell Phone View	Support Iphone,Android cell phone view .
	IP Camera Control Centre Software	Support 1,4,9,16,25,36 channel monitoring in one screen, no channel limited ,Support centralized monitor, remote record, playback and alarm settings.
Lens	Lens Type	3.6mm Glass Lens
Video	Image Compression	MJPEG
	Image Frame Rate	15fps(VGA),30fps(QVGA)
	Resolution	640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	Light Frequency	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
	Night Visibility	36 IR LEDs, Night visibility up to 65'
	Filter Switch	Built-in IR Cut,With self-check function,Double optical filter automatic switch, no color deviation indoor or outdoor.
Network	Ethernet	One 10/100Mbps RJ-45
	Supported Protocol	HTTP,FTP,TCP/IP,UDP,SMTP,DHCP,PPPoE,DDNS,UPnP etc.
	IP Mode	Dynamic IP address, static IP address, PPPOE
	Online Visitor	Support 4 visitors at the same time
Wireless	Wireless Standard	IEEE 802.11b/g/n
	Wireless Security	WEP, WPA, WPA2 Encryption
Others	Housing	Metal
	Power	DC12V 1A
	Working Temperature	14-122°F
	Working Humidity	95% RH
	Size	7.5"L x 3"H
	Weight	2 Lbs.
	Accessories	Adaptor, CD(including manual), Bracket,Screw
Alarm	Alarm Action	Support Email photo, FTP photo etc.
System	Supported OS	Microsoft Win98 SE/ME/2000/XP/Vista/Windows7/Mac OS.
	Browser	IE6.0, IE7.0, IE8.0, FireFox, Google or other standard browser
Certification	CE,FCC,RoHS	

Package Includes:

- 1 IP Camera
- 1 Mounting bracket
- 1 Software CD
- 1 12VDC Power supply
- 1 Bag of mounting hardware
- 1 Instruction Manual

Ordering Information:

ST-EVO-BT3.6 IP Bullet Camera