

Features:

- 1/3" CMOS Sensor
- 300,000 Pixel
- MJPEG Compression
- WiFi Capable
- 3.6mm Lens
- 50 Foot IR capability
- Indoor housing
- Power supply included



Specifications:

Features	System Security	Supports three-level account, password, user authority management
	Cell Phone View	Supports Iphone,Android cell phone view .
	IP Camera Control Centre Software	Supports 1,4,9,16,25,36 channel monitoring in one screen, no channel limited ,Support centralized monitor, remote record, playback and alarm settings.
Lens	Lens Type	Glass Lens Standard : 3.6 mm
Video	Image Compression	MJPEG
	Image Frame Rate	15fps(VGA),30fps(QVGA)
	Resolution	640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	Light Frequency	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
	Night Visibility	22 IR LEDs, Night visibility up to 50 Feet
Network	Filter Switch	Built-in IR Cut,With self-check function,Double optical filter automatic switch, no color deviation indoor or outdoor.
	Ethernet	One 10/100Mbps RJ-45
	Supported Protocol	HTTP,FTP,TCP/IP,UDP,SMTP,DHCP,PPPoE,DDNS,UPnP etc.
	IP Mode	Dynamic IP address, static IP address, PPPOE
	Online Visitor	Support 4 visitors at the same time
Others	Product Type	Suspended ceiling Dome / Indoor use
	Power	DC12V 1A
	Working Temperature	14 - 122 °F
	Working Humidity	95% RH
	Size	5"W x 4"H
	Weight	1.25 lbs.
	Accessories	Adaptor, CD(including manual), Bracket, Screw
Alarm	Alarm Action	Support Email photo, FTP photo etc.
System	Supported OS	Microsoft Win98 SE/ME/2000/XP/Vista/Windows7/Mac OS.
	Browser	IE6.0, IE7.0, IE8.0, FireFox, Google or other standard browser
Certifications	CE,FCC,RoHS	

Package Includes:

- 1 IP Camera
- 1 Software CD
- 1 12VDC Power supply
- 1 Bag of mounting hardware
- 1 Instruction Manual

Ordering Information:

ST-EVO-D3.6-W IP Dome Camera