

Features:

- 1/3" CMOS Sensor
- 300,000 Pixel
- MJPEG Compression
- WiFi Capable
- 4mm - 9mm, 2X Optical zoom
- 50 Foot IR capability
- Vandal proof, indoor housing
- Power supply and wall mount housing included



Specifications:

Features	System Security	Supports three-level account, password, user authority management
	Cell Phone View	Supports Iphone, Windows Mobile, Symbian, Android cell phone view.
CPU	Processor	32Bit RSIC Embedded Processor
Video	Compression Format	M-JPEG
	Signal System	CMOS 300,000 pixel
	Frame Rate	25fps
	Resolution	VGA(640*480), QVGA(320*240)
	Video Adjustment	Brightness and contrast adjustable, Auto White Balance, Auto Backlight Compensation
	Lens	Standard : 4-9mm
	Zoom	4 Level automatic zoom
Nightvision	Filter Switch	Built-in IR Cut, With self-check function, Double optical filter automatic switch, no color deviation.
	Nightvision	22 IR LEDs IR distance: 50 Feet
Pan/Tilt	Rotation Angle	Pan: 355°, Tilt: 90°
	Rotation Speed	Pan: 5°- 50°/ Second Tilt: 5°-30°/second
	Preset	Web Browser: 16 preset positions
Network	Network Interface	RJ-45 10/100Mb self-adaptable Ethernet slot
	Wireless	WIFI, 802.11 b/g
	Protocol	Supports TCP/IP,HTTP,ICMP,DHCP,FTP,SMTP,PPPoE etc.
	Online Visitor	Supports 4 visitors at the same time
	IP Mode	Dynamic IP address, Static IP address, PPPOE
Others	Material	Dome cover: PMMA, Dome body: Aluminium alloy
	Environment	Indoor use
	Power	DC12V 1A
	Working Temperature	14~122 °F
	Working Humidity	95% RH
	Size	Item size: 5"W x 5"H x 5"D
	Weight	3.65 lbs.
Alarm	Accessories	Adaptor, CD (including manual), Bracket, Screw
	Alarm Action	Supports Email photo, FTP photo etc.
System	System Requirement	Microsoft Win98 SE/ME/2000/XP, Vista, Win 7, Browser: IE6.0, IE7.0, IE8.0, Fire Fox, Google Browser or other standard browser

Package Includes:

- 1 IP Camera
- 1 Software CD
- 1 12VDC Power supply
- 1 Bag of mounting hardware
- 1 Instruction Manual

Ordering Information:

ST-EVO-IRMINI-W IP Mini PTZ Camera