

ST-HDC2FTD

2MP HD-TVI Fixed Lens IR Turret Dome Camera



**HD-TVI High Definition
video over coaxial cable**

Features:

- 2MP High Resolution
- Incorporates HD-TVI to provide HD 1080p video over coaxial cable
- 3.6mm or 2.8mm Fixed lens
- True Day/Night
- Smart IR
- IR Distance up to 131 Feet
- On Screen Display menu
- IP66 Weather rating



Camera

Image sensor	2MP CMOS Image Sensor
Effective Pixels	1928(H) x 1088(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR on
Shutter Time	1/25s to 1/50,000s
Lens	3.6mm or 2.8mm Fixed lens
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0-360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 turbo HD output
S/N Ratio	More than 62dB



Menu

AGC	Supported
D/N Mode	Color/BW/Smart IR
White Balance	Auto/Manual
BLC	Supported
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, Smart IR

General

Working Temperature/Humidity	-40 °C – 60 °C (-40 °F – 140 °F)
Humidity	90% or less (non-condensing)
Power Supply	12 VDC (not included)
Power Consumption	Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 131 Feet
Communication	Up the coax
Dimensions	110 × 93.2mm (4.33" × 3.67")
Weight (approximate)	350g (0.77 lbs.)



ST-WM2
Wall mount



ST-JB2
Junction box

Ordering Information:

ST-HDC2FTD	2MP HD-TVI 3.6mm Fixed Lens IR Turret Dome Camera
ST-HDC2FTD-2.8	2MP HD-TVI 2.8mm Fixed Lens IR Turret Dome Camera