

ST-IP-BT3.6 Series Fixed Lens IP Bullet Cameras

Features:

- 1/4" 1 Megapixel progressive scan CMOS sensor (ST-IP-BT3.6-1)
- 1/3" 2 Megapixel progressive scan CMOS sensor (ST-IP-BT3.6-2)
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@720P(1280×720)
- DWDR - Digital Wide Dynamic Range
- Day/Night(ICR), 3DNR,AWB,AGC,BLC
- Multiple network monitoring: Web viewer, SPSS, CMS(DSS/PSS) & DMSS
- 3.6mm fixed lens
- Max. IR LEDs Length 65 Feet
- IP66 Rated housing
- 2 Year Warranty

Description:

The Securitytronix ST-IP-BT3.6 series cameras are professional series 1 and 2 Megapixel IP cameras featuring either a 1/4" (1MP) or 1/3" (2MP) CMOS sensor and a fixed 3.6mm lens. This camera is perfect for day and night applications, the IR LEDs provide illumination of objects up to 65' away. Powering can be achieved through an external 12VDC power supply or via a separate PoE (Power over Ethernet) switch. The ST-IP-BT3.6 series are ONVIF Profile 'S' (Open Network Video Interface Forum) compliant. The IP66 outdoor housing can be wall or ceiling mounted.



ST-IP-BT3.6-1 Specifications:

Camera	
Image Sensor	1/4" 1 Megapixel progressive scan CMOS
Effective Pixels	1280(H) x 720(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
Min. Illumination	0.1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W); 0Lux/F1.2(IR on)
S/N Ratio	More than 50dB
Camera Features	
Max. IR LEDs Length	65'
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm Fixed, Max Aperture F1.6
Focus Control	Manual
Angle of View	H: 70°(48°/36°)
Video	
Compression	H.264/MJPEG
Resolution	720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240)
Frame Rate	Main Stream 720P(1 ~ 25/30fps) Sub Stream D1/CIF(1~25/30fps)
Bit Rate	H.264:56K ~ 8192Kbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Compatibility	ONVIF, CGI, PSIA
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
General	
Power Supply	DC12V,PoE (802.3af)
Power Consumption	<4W
Working Environment	-22°F~+140°F, Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	N/A
Dimensions	2.75" x 2.6" x 6.2"
Weight	1.1Lbs

Ordering Information:

ST-IP-BT3.6-1 IP Bullet Camera, 1 Megapixel, Fixed 3.6mm Lens
ST-IP-BT3.6-2 IP Bullet Camera, 2 Megapixel, Fixed 3.6mm Lens

ST-IP-BT3.6-2 Specifications:

Camera	
Image Sensor	1/3" 3Megapixel progressive scan CMOS
Effective Pixels	2048(H) x 1536(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3(4)~1/10000
Min. Illumination	Color: 0.1Lux/F1.6; 0Lux/F1.6 (IR on)
S/N Ratio	More than 50dB
Camera Features	
Max. IR LEDs Length	65'
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC /HLC /DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	3.6mm Fixed, Max Aperture F1.6
Focus Control	Manual
Angle of View	H: 71.9°/45.3°
Video	
Compression	H.264H/H.264B/H.264/ MJPEG
Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480) /CIF(352×288/352×240)
Frame Rate	Main Stream 1080P(1 ~ 25/30fps) Sub Stream D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264H: 16K ~ 8192Kbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Compatibility	ONVIF, CGI, PSIA
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	Max 4W
Working Environment	-22°F~+140°F, Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	N/A
Dimensions	2.75" x 2.6" x 6.2"
Weight	1.1Lbs

Package Includes:

1 IP Camera, 1Software CD, 1 Operation manual, 1 Mounting hardware