

ST-IP-BT*VF-PRO Series IP Bullet Cameras

Features:

- High resolution 1/4", 1.0 or 2.0 Megapixel CMOS Sensor
- Integrated 2.8 - 12.0 mm Megapixel lens, 4X Zoom
- 98 Foot IR Range for day and night applications
- H.264 Compression
- Two-way audio
- Hardware motion detection
- DC 12V or Power over Ethernet (IEEE 802.3af)
- Wall mountable IP66 Indoor/Outdoor Housing
- ONVIF Compliant



Description:

The Securitytronix ST-IP-BT*VF-PRO cameras are a professional series One or Two megapixel IP camera featuring a 1/4" CMOS sensor and integrated 4x zoom 2.8 - 12.0mm lens. This camera is perfect for day and night applications, the IR LEDs provide illumination of objects up to 98' away. Powering can be achieved through the included 12VDC power supply or via a separate PoE (Power over Ethernet) switch. The ST-IP-BT*VF-PRO also features two way audio, hardware motion detection and is ONVIF (Open Network Video Interface Forum) compliant. The IP66 outdoor housing is equipped with an adjustable sunshield and included pivoting wall mount.

Specifications:

ST-IP-BT1VF-PRO Device Type	720p, 1MP 9P006	Audio	Microphone input and line out, Supports two-way voice intercom equipment
ST-IP-BT2VF-PRO Device Type	1080p, 2MP 9P006	Audio in/out	1 ch audio input, 1 ch audio output
Sensor	1/4 inch CMOS	Audio Compression	G.711/G.726
Day and Night	Yes	Alarm in/out	1ch alarm input, 1 ch alarm output
Min. Scene Illumination	0.5 lux (0 Lux IR ON)	Alarm Trigger	Motion Detection
Infrared sensitivity	Supported	Alarm processing	Control center to monitor. Email, log record, SD card storage etc.
IR Filter	IR-CUT	Protocol	HTTP, TCP/IP, UDP, SMTP, DDNS, DNS, SNTP, DHCP, FTP, RTP, RTSP, UPNP, ONVIF, 28181
IR LED	Yes	Ethernet Safety	(10/100 Base-T), RJ-45 connector IP address filtering, User level password protection, User access log
IR distance	98 Feet	Web Browser	IE 6.0 and above, Google, Firefox etc.
Electronic shutter	1/5-1/15,000 /S	Mobile Phone	Support iPhone Android, Bit rate: 32K – 512K adjustable, Frame rate: 6–12 fps
Lens	2.8mm - 12mm	Software Management	CMS and ONVIF compatible devices
Focus	Automatic	Event Action	Send E-mail, Send SMS, Zoom in alarm, Pop up map, Go to PTZ preset pos etc.
Aperture	Fixed Aperture F1.2	Remote Access	DDNS, Software
Compression	H.264 Main Profile/Baseline	Power Consumption	DC 12V, <2W
ST-IP-BT1VF-PRO Resolution	1280*720@30fps	Temperature	-4° ~ 140°F
ST-IP-BT2VF-PRO Resolution	1280*720@30fps	Humidity	10~85%
Stream flow	Supports dual stream	Dimension	10" x 3.25"
Bit Rate	128-8192kbps	Certification	CE ,FCC
Bit Rate Type	CBR/VBR		
S/N Ratio	>50DB		
Image enhancement	Auto White Balance, Backlight Compensation, Brightness, Contrast, Saturation adjustment		
Subtitles	Channel name, Date, Time		
Flip Config	Up/down, Left/right		

Ordering Information:

ST-IP-BT1VF-PRO	IP Bullet Camera, 1 Megapixel, Varifocal Lens
ST-IP-BT2VF-PRO	IP Bullet Camera, 2 Megapixel, Varifocal Lens

Package Includes:

1	IP Camera	1	Power supply
1	Software CD	1	Network cable
1	Operation manual	1	Screw bag