

ST-IP-D2VF-W IP Dome Camera 2 Megapixel, Varifocal Lens

Features:

- High resolution 1/4", 2.0 Megapixel CMOS Sensor
- Integrated 2.8-12.0 mm Megapixel lens, 4X Zoom
- 65 Foot IR Range for day and night applications
- H.264/MJPEG compression
- Real time transmission up to 15FPS@2MP
- Two-way audio
- Hardware motion detection
- DC 12V or Power over Ethernet (IEEE 802.3af)
- Wall/Ceiling mountable IP66 Indoor/Outdoor Housing
- ONVIF Compliant



Description:

The Securitytronix ST-IP-D2VF is a professional series Two megapixel IP dome camera featuring a 1/4" CMOS sensor and integrated 4x zoom 2.8 - 12.0mm lens. This camera is perfect for day and night applications, thirty infrared LEDs provide illumination of objects up to 65' away. It's H.264/MJPEG compression allows for real time transmission of up to 15 frames per second at Two megapixels. Powering can be achieved through the included 12VDC power supply or via a separate PoE (Power over Ethernet) switch. The ST-IP-D2VF also features two way audio, hardware motion detection and is ONVIF (Open Network Video Interface Forum) compliant. The IP66 outdoor housing can be ceiling or wall mounted as needed.

Specifications:

Sensor	2.0 Megapixel CMOS Sensor
Size	1/4 inch
Effective Pixels	2MP 1600 x 1200, 1MP 1280 x 720
Lux	0.5 Lux
IR Sensitivity	Yes
IR Cut Filter	Yes
Lens	2.8-12.0mm Auto zoom lens
Viewing Angle	22° - 90° (Horizontal)
Linux System	Internal Linux system
IR distance	65 Feet
Motion Detection	Yes
Electronic Shutter	1/5 - 1/15,000 sec
Back Light Control	Yes
Gain Control	Auto
White Balance	Auto
S/N Ratio	>50 dB
Video Compression	H.264
Picture Resolution	UXGA 1600 x 1200, HD 1280 x 720
Bit Rate	80 K~ 2.0 M bps

Image Frame Rate	15 FPS
Audio Compression	G.711
Two way audio	Yes
Alarm I/O	1 channel in/out
Mount Type	Ceiling/Wall Mountable
Ethernet	Ethernet (10/100 Base-T), RJ-45 connector
Protocol	TCP,UDP,IP,HTTP,FTP,SMTP,DHCP,DNS, ARP,ICMP,POP3,NTP,RTP, and RTCP
Web Browser	Microsoft Internet Explorer 6.0 above
SDK	SDK-H
Security	Administrator password protection
Weather Rating	IP66
Operating Temperature	-22° - +140°F
Operating Humidity	10 - 85%
Powering Options	PoE (IEEE802.3af) or 12VDC
Power Consumption	10-12W (DC 12V,1A)
Dimensions	5.25" H x 6.0"W
Weight	2.6 lbs.
Certifications	CE ,FCC

Ordering Information:

ST-IP-D2VF-W IP Dome Camera, 2 Megapixel, Varifocal Lens

Package Includes:

- 1 IP Camera
- 1 Software CD
- 1 12VDC Power supply
- 1 Bag of mounting hardware
- 1 Quickstart guide