

ST-IP-D*PRO Series IP Dome Cameras

Features:

- Includes Eye View Smart (EVS) Intelligent NVR Software
- High resolution 1/3", 1.3 or 2.4 Megapixel Aptina CMOS Sensor
- Integrated 2.8 - 12.0 mm Megapixel lens, 4X Zoom
- 65 Foot IR Range for day and night applications
- 0.1 Lux Color, 0 Lux black & white
- H.264/JPEG Compression
- Ceiling / Wall mountable IP66 Indoor / Outdoor Vandalproof housing
- DC 12V, 1,000 mA or external Power over Ethernet (IEEE 802.3af)
- ONVIF 2.0 Compliant



Description:

The Securitytronix ST-IP-D*PRO series cameras are professional series 1.3 or 2.4 megapixel IP cameras featuring a 1/3" CMOS sensor and integrated 4x zoom 2.8 - 12.0mm lens. This camera is perfect for day and night applications, the IR LEDs provide illumination of objects up to 65' away. Powering can be achieved through an external 12VDC power supply or via a separate PoE (Power over Ethernet) switch. The ST-IP-D*PRO is ONVIF 2.0 (Open Network Video Interface Forum) compliant. The IP66 outdoor housing can be wall or ceiling mounted.

Specifications:

ST-IP-D1.3PRO-* Device Type	1.3 Megapixel
ST-IP-D2.4PRO-* Device Type	2.4 Megapixel
Sensor	1/3 inch Aptina CMOS
Lens	2.8 - 12mm Manual Zoom Lens
1.3MP Resolution	960p@25fps, 720p@25fps, D1@25fps
2.4MP Resolution	1080p@25fps, 720p@25fps, D1@25fps
Min. Scene Illumination	0.1 lux (0 Lux IR ON)
S/N Ratio	>50DB
Focus	Manual
Day and Night	IR Cut filter with auto switch
Number of IR Emitters	21
IR Range	65 Feet
Delay	Within the LAN 0.3S
Video Compression	H.264 / JPEG
Protocol	TCP, UDP, RTSP, FTP, PPPOE, DHCP, DDNS, NTP, UPnP, SMTP
Onvif	Supports Onvif 2.0
User Permission	Multi-user Classification Management
Connection	1 RJ45 10/100Mbps Ethernet Interface
Weather Rating	IP66
Dimensions	6.0" x 4.25"
Weight	2.65 lbs.
Operating Temperature	-4° ~ 122°F
Power	12VDC / 1,000 mA (Not Included)
Consumption	3.0 Watts
Humidity	10 ~ 90%, non-condensing

Eye View Smart (EVS) Intelligent NVR Software is included with these cameras at no extra charge!



ST-NVR-EVSPRO Software Features:

- Network Video Recording software for a remote or onsite computer
- 32 Channels of live viewing
- Live view built-in motion & I/O analytics
- 4 Channel playback
- Single server remote client
- 16 Channels of remote live viewing
- 4 Channels of remote playback
- Fixed stream profile
- Supports mobile devices
- 1 Layer E-map support
- Can be upgraded to EVS PRO+ version to add more features

Ordering Information:

ST-IP-D1.3PRO-W	IP Dome Camera, 1.3 Megapixel, Varifocal Lens, white housing
ST-IP-D1.3PRO-B	IP Dome Camera, 1.3 Megapixel, Varifocal Lens, black housing
ST-IP-D2.4PRO-W	IP Dome Camera, 2.4 Megapixel, Varifocal Lens, white housing
ST-IP-D2.4PRO-B	IP Dome Camera, 2.4 Megapixel, Varifocal Lens, black housing

Package Includes:

1	IP Camera
1	Software CD
1	Operation manual