

ST-PTZ550-27 Pan-Tilt-Zoom Camera

Features:

- 1/4" Sony CCD Sensor
- 3.5 - 94mm Zoom Lens
- IR Sensitive, Auto ICR
- D/N 27X Optical Zoom, 12X Digital Zoom
- Color: 550TVL, 0.1 Lux; B/W: 680TVL, 0.02Lux
- Precise preset positions, low noise design, two-tier metal structure
- Built in constant temperature system
- 256 Preset positions with 8 privacy zones
- Standard wall mount included
- Power supply included
- IP66 Weather Rating



Only 8.0" Wide

The ST-PTZ550-27 is a professional grade dome color camera with pan, tilt and zoom (PTZ) capability of 540TVL of resolution in color and 680TVL in black & white. The camera's full digital design allows the saving of all settings in non-volatile memory. Its 256 preset positions allow up to 8 privacy zones and up to 8 sector label displays. The ST-PTZ550-27's mechanical design permits continuous horizontal 360° rotation and 0 to 90° vertical rotation. Additional features of this camera include an internal auto temperature system, 27X optical zoom and 12X digital zoom. The ST-PTZ550-27 is compatible with PELCO-D/P protocol.

Specifications:

Address:	0 - 255	Vector Scan Groups :	6 programmable
Pan range:	360° continue	Integrate Multi-protocol:	Pelco-D/P Selectable
Tilt Rotation Range:	0° - 90° flip	Auto Scan:	Smart programmable variable speed
Manual Speed Pan:	0.1° - 300°/sec	3-Dimension scan:	Yes
Manual Speed Tilt:	0.1° - 120°/sec	Long-focus speed-limited:	Yes
Preset Speed:	400°/sec	Power off real-time memory:	Yes
Preset Accuracy:	± 0.10°	Home Position:	Yes
Preset Points:	128 points	Camera Menu operation:	Yes
Operation Menu:	Multi-Language	Manual operation:	Endless
Function Display:	Yes	IP66 for Outdoor use:	Outdoor/ Indoor
Crosshair Function:	Yes	Operating humidity:	≤95%
Pan and tilt position display:	Yes	Heater:	43°F on - 57°F off
Privacy Zones:	8 programmable zones	Power:	AC24V/3A (included)
Sector Label Display:	8 programmable zones	Video Connection:	BNC
Recall Function:	Yes	Power Consumption:	35W
Operation return function:	Yes	Communication:	RS485
PTZ Tours:	3 programmable (pan/tilt/zoom and each tour is 120 seconds)	Operation Temp:	-4°F - 122°F
		Dimensions:	8.0"W x 14.5"H

Optional Accessories:

ST-PTZCORNER	Corner mount bracket
ST-PTZPOLE	Pole mount bracket
ST-PTZPEND94	Pendant mount

Ordering Information:

ST-PTZ550-27 Pan-Tilt-Zoom Camera