

DT-QAM-AMM-1

Single Channel Agile Micro Modulator

The DataTronix DT-QAM-AMM-1, High Definition (HD) Modulator, is the ultimate solution for adding local content seamlessly into a coaxial cable TV network. This innovative device boasts the ability to generate an MPEG-2 encoded signal in either QAM or ATSC format from an HDMI input. With its sleek design, it features one HDMI input, one RF output, and one LAN port for web management - making it the perfect addition to add locally generated content, such as digital signage and video surveillance.

This innovative unit can be effortlessly installed into an existing analog micro-modulator slot, making upgrading your system to HD an effortless process.

Key Features

- QAM Channels: 2 - 135
- ATSC Channels: 2 - 69
- Output: 41 dBmV
- Impedance: 75 Ohms
- RF Output: "F" Type, Female



| Specifications | |
|--------------------------|-------------------------------|
| Input | |
| Video Input | HDMI |
| Audio Input | HDMI |
| Video Input Format | 480i/p, 576i/p, 720p, 1080i/p |
| Closed Captioning (CC) | Composite Video |
| RF Output | |
| Frequency Range | 57-861 MHz |
| Output Level | 41 dBmV |
| Channel Bandwidth | 6 MHz |
| Channel Level Adjustment | 0 dB - 30 dB Typically |
| MER | 35 dB Typically |
| Attenuation Step | 1 dB per step |
| Compression | |
| Video | MPEG 2 |
| Video Resolution | 1080p 25/30 Max |
| Video Bit Rate | 18Mbit/sMax |
| Audio | MPEG - 1 Layer 2, AAC-LC, AC3 |

| Connections | |
|------------------------|---|
| HDMI IN | HDMI IN |
| Closed Captioning (CC) | RCA Female 75Ω (Yellow) |
| RF Out | 1 RF Output, Type Female, 75Ω |
| LAN | Web Management |
| Button Control | UP/Down/OK |
| Micro USB-B | S/W Update |
| General | |
| Modulation | Standard QAM (J83 Annex B)/ ATSC A/53 |
| | Constellation 256 QAM, 64 QAM/8VSB |
| | Bandwidth 6MHz |
| | Channel Type: STD |
| DC IN | 5VDC, 12VDC |
| Display | OLED panel @ 64 x 32 Dots |
| Operating Limits | Temperature: 41-104°F (5-40°C) |
| | Relative Humidity 80% @ 86°F (30°C) |
| Dimensions | 9.25" x 1.06" x 3.46" (235 x 27 x 88 mm) |
| Weight | 0.6294 lbs (0.2855 kg) |
| Warranty | 2 Year Warranty |