



Hospitality Value Series LED HDTV

32" LED Model J32LV840
40" LED Model J40LV840
42" LED Model J42LV840
49" LED Model J49LV840



Anti-Theft
Base



Pro Idiom
MPEG4



Adjustable
Swivel Base



Volume
Limiter



IR
Pass-thru



USB Clone
Programming



Commercial
Interface



Eco-
Friendly



2-Year
Replacement



Ad
Splash

SPECIFICATIONS

J32LV840 - 32" LED HDTV

| | |
|-------------------------|-----------------------|
| Cabinet Color | flat black |
| Screen Size | 32" diagonal |
| Display Resolution | 1366 x 768 |
| Brightness (typical) | 300 cd/m ² |
| Viewing Angle | 178° x 178° |
| Response Time (typical) | 8 ms |
| Broadcast System | NTSC/ATSC/QAM |
| Max Audio Output | 2 x 8 W |
| VESA Standard | 200 mm x 200 mm |
| Power Supply | AC 100-240V 60Hz |
| Power Consumption | <38 W |
| Standby Consumption | <1 W |
| TV & Stand (WxHxD) | 29x1 x 19.2 x 8.1" |
| TV w/o Stand (WxHxD) | 29.1x17.4x3.5" |
| Set Weight | 12.4 lbs. |
| Shipping Weight | 16.8 lbs. |

J40LV840 - 40" LED HDTV

| | |
|-------------------------|-----------------------|
| Cabinet Color | flat black |
| Screen Size | 39.5" diagonal |
| Display Resolution | 1920 x 1080 |
| Brightness (typical) | 300 cd/m ² |
| Viewing Angle | 176° x 1760° |
| Response Time (typical) | 8.5 ms |
| Broadcast System | NTSC/ATSC/QAM |
| Max Audio Output | 2 x 10 W |
| VESA Standard | 200 mm x 200 mm |
| Power Supply | AC 100-240V~ 60Hz |
| Power Consumption | <43 W |
| Standby Consumption | <1 W |
| TV & Stand (WxHxD) | 36 x 23.3 x 8.8" |
| TV w/o Stand (WxHxD) | 36 x 21.4 x 3.3" |
| Set Weight | 20.1 lbs. |
| Shipping Weight | 24.6 lbs. |

J42LV840 - 42" LED HDTV

| | |
|-------------------------|-----------------------|
| Cabinet Color | flat black |
| Screen Size | 42" diagonal |
| Display Resolution | 1920 x 1080 |
| Brightness (typical) | 300 cd/m ² |
| Viewing Angle | 178° x 178° |
| Response Time (typical) | 6.5 ms |
| Broadcast System | NTSC/ATSC/QAM |
| Max Audio Output | 2 x 10 W |
| VESA Standard | 200 mm x 200 mm |
| Power Supply | AC 100-240V 60Hz |
| Power Consumption | <65 W |
| Standby Consumption | <1 W |
| TV & Stand (WxHxD) | 38.3 x 24.6 x 8.6" |
| TV w/o Stand (WxHxD) | 38.3 x 22.4 x 3.5" |
| Set Weight | 24.25 lbs. |
| Shipping Weight | 30.42 lbs. |

J49LV840 - 49" LED HDTV

| | |
|-------------------------|-----------------------|
| Cabinet Color | flat black |
| Screen Size | 49" diagonal |
| Display Resolution | 1920 x 1080 |
| Brightness (typical) | 300 cd/m ² |
| Viewing Angle | 178° x 178° |
| Response Time (typical) | 6.5 ms |
| Broadcast System | NTSC/ATSC/QAM |
| Max Audio Output | 2 x 10 W |
| VESA Standard | 200 mm x 200 mm |
| Power Supply | AC 100-240V~ 60Hz |
| Power Consumption | 80 W |
| Standby Consumption | <1 W |
| TV & Stand (WxHxD) | 43.7 x 27.5 x 10.25" |
| TV w/o Stand (WxHxD) | 43.7 x 25.5 x 3.5" |
| Set Weight | 30.2 lbs. |
| Shipping Weight | 35.5 lbs. |

Commercial Features

| | |
|-------------------------------|--|
| Ultra-Slim Bezel | New thin bezel with reduced weight. |
| Channel Labeling | Allows channels to have individual customized names |
| Initial Channel | Sets the input/channel for the TV to tune when turned on |
| Volume Limiter/Initial Volume | Sets the maximum and initial volume settings when the TV is turned on |
| USB Cloning Capable | Allows duplication of TV configuration for easy installation |
| Ad \$plash | Display short advertisements on TV based on schedule settings |
| Master & Guest Remotes | Separate remotes for configuration and operation |
| Front Panel/Menu Lockout | Disables front panel and menu controls |
| Power On/Off Scheduler | Sets recurring time for the TV to power on and off |
| Energy-Saving Features | Auto power-off, less than 1 watt in standby mode, low power LED, no signal power-off |
| VESA Mount Pattern | Wall mount your TV using standard mounts |
| IR Pass-Thru | Allows control of an external device without the need for direct line of sight |
| Bed 1/2/3 Capable | Allows simultaneous control of multiple TVs in the same room without remote interference |

| | |
|----------------------|---|
| Antenna/Cable Merge | Ability to merge antenna and cable channels into a single channel line-up |
| Auto Detect Side A/V | Allows users to easily connect peripheral devices to side input without use of remote |
| Last Power Mode | Selectable power state of the TV after a power outage |

Accessories

| | |
|-------------------------|-------------------------|
| User Remote (R230D1) | Included |
| Master Remote (R230D2) | Not Included (Optional) |
| Direct TV DRE Kit | Not Included (Optional) |
| Anti-Theft Swivel Stand | Included |
| Security Lock Kit | Included |

Certifications

| | |
|--------------------|-----|
| FCC, RoHS, UL, CEC | Yes |
|--------------------|-----|

Service/Limited Warranty

| | |
|------------------|--|
| Limited Warranty | Two-Year replacement, provides for minimal downtime by offering advance replacement shipping instead of on-site repair |
|------------------|--|

Note: Features and specifications are subject to change without notice.



Anti-Theft Base



Swivel Base Design

