



ST-LCDCCTV-17H 17" CCTV LCD Monitor With BNC & VGA Inputs

Features:

- One BNC, one HDMI & one VGA video input
- One 3.5mm Audio input
- Looping outputs for BNC video & 3.5mm audio
- Resolution up to 1280 x 1024
- Up to 700:1 contrast ratio
- 250-nit brightness
- 1 Year warranty



The ST-LCDCCTV-17H 17" monitor features multiple inputs that enable the use of one monitor instead of multiple monitors providing a cost savings in many applications. This monitor has a BNC analog video input, one HDMI input, one VGA input and 1 3.5mm audio input as well as a BNC and 3.5mm audio loop through outputs. With a maximum resolution of 1280 x 1024 and a high contrast ratio of 700:1 the CT-LCDCCTV-17H offers razor sharp, vivid images. A high brightness level maximizes the monitors high resolution and contrast resulting in outstanding image detail.

Specifications:

LCD Display	17" Active matrix TFT
Dot Pitch	0.264 x 0.264mm
Contrast Ratio	700:1
Brightness	250cd/m ²
Response Time	Tr 7 ms; Tf 11ms (typ)
Viewing Angle	L/R: 80° +/-10°, U/D: 80° +/-10°
Display Color	16.777 Million
PC Interface	15 Pin D-sub, RGB, 0-0.7Vpp, RGB Analog, 75 Ohms terminated
Video Sync.	TTL Positive or negative
Display Mode	VGA, SVGA, XGA, SXGA
Max Resolution	1280 (H) x 1024 (V) SXGA
Video Connections	(1) VGA, (1) HDMI, (1) BNC in, (1) BNC out
Audio Connections	(1) 3.5mm in, (1) 3.5mm out
OSD Controls	Yes
Scan Frequency	Horizontal: 31.5 - 80 KHz Vertical: 56 - 75 Hz
Power Adaptor	Input: AC 100-240V, 50-60Hz, 1.6A Output: DC, 12V, 4.16A
Power Consumption	48W Maximum
Operating Conditions	32 - 104°F, Humidity 20% - 85%
Storage Conditions	-4 - 140°F, Humidity 10% - 95%
Speakers	2W x 2 Box inside design
Certifications	BSMI, FCC, CE, UL, CUL
Monitor Dimensions	15.5"W x 12.5"H x 2.5"D (without stand)
Box Dimensions	19"W x 16.5"H x 7.5"D
Weight	10.6 lbs.